

RE7
GOLD LVP

WW706 Genuine +



7063 Accent Pine




150 Cinnamon Walnut

Color Variation: V3 -
Moderate



154 Almond Oak

Color Variation: V3 -
Moderate



203 Tawny Oak

Color Variation: V4 -
Substantial



556 Smoky Oak

Color Variation: V4 -
Substantial



591 Oyster Oak

Color Variation: V4 -
Substantial


RE7

GOLD LVP

WW706 Genuine +

Construction	SPC	
Profile	Click	
Size	7" x 48"	17.78 cm x 121.92 cm
Overall Thickness	0.173"	4.4 mm
Wear Layer Thickness	20 mil (0.02")	0.5 mm
Attached Underlayment Thickness	0.039"	1 mm
Finish	ArmourBead®	
Edge Description	Micro Bevel	
Area per Carton	27.73 sq ft	2.58 sq m
Area per Pallet	1525.15 sq ft	141.69 sq m
Installation Methods	Floating	
Installation Grade	Above, On, Below	
Residential Warranty	Lifetime	
Commercial Warranty	10 Year Light Commercial	
Installation	Floorte Pro 3 & 5 Series Installation Floorte Pro 6, 7 & 10 Installation	
Radiant Panel (ASTM E648)	Passes, Class I	

Coordinating Trim

				
Baby Threshold*	T-Molding*	Multi-Purpose Reducer	Quarter Round	Flush Stairnose
BT3HS 94" VSBT2 94"	VHTMD 94"	VHMPR 94"	VSQT1 94"	VFSN4 94"

*Packaged with molding track

Coordinating Metal Trim

			
Finish	Reducer	T-Mold	Stair Cap
Satin Silver	143SA	146SA	140SA
Satin Nickel	144SA	147SA	141SA

Installation Range

Profile Size	Installation Range
3.5mm	1.5mm to 3.5mm heights
5.5mm	3.6mm to 5.5mm heights
8mm	6mm to 8mm heights