

RE7

SILVER ENGINEERED

WW656 Smart



1102 Biscuit Lg



135 Rustic Natural




223 Caramel




543 Weathered



780 Gunstock



874 Hazelnut



938 Coffee Bean



947 Cherry



1102 Biscuit Lg



5013 Charcoal



7011 Chocolate



7087 Flax Seed Lg



7091 Kona Lg

RE7

SILVER ENGINEERED

WW656 Smart

Construction	Engineered	
Species	Red Oak	
Nominal Overall Thickness	3/8"	8.2 mm
Nominal Width	5"	127 mm
Maximum Length	Random lengths up to 58.5"	Random lengths up to 148.59 cm
Finish	ScufResist Platinum	
Gloss Level	20%	
Surface Texture	Smooth	
Edge Description	Micro Bevel	
End Description	Mb	
Profile	Tongue And Groove	
Weight per Carton	34.5 lbs	15.64 kg
SQFT per Carton	23.66 sq ft	2.19 sq m
SQFT per Pallet	1419.6 sq ft	131.88 sq m
Installation Methods	Nail, Staple, Glue, Floating	
Installation Grade	Above, On, Below	
Variation	High	
GREENGUARD® Certified	Yes	
Cradle-to-Cradle Certified	Yes	
Radiant Heat Approved	Yes	
Residential Warranty	Lifetime	
Commercial Warranty	5 Year Commercial	
Installation	Duras/Epic + Epic Extreme Hardwood Flooring Installation Guidelines	
Maintenance	Hardwood Maintenance Guidelines	
All measurements are nominal.	Cartons may include random lengths.	

Features

Classic hardwood flooring in both traditional and modern colors. This oak hardwood floor showcases the charm and natural beauty of hardwood, accentuated with a wide range of character. Offered in 3 1/4" and 5" widths.

Suggested Adhesive

Style Name	Style Number
35MC	HS105
Urebond Plus	SWADH

Trim Pieces length: 78" (*Overlap Reducer and Overlap Stairnose are designed for floating installations only. These items are non-stocking - but are available through a quick-ship program. Delivery should take approximately 2 to 3 weeks.)



SFR18

Flush Reducer



SRO18

*Overlap Reducer



SFS18

Flush Stairnose



SSO18

*Overlap Stairnose



SCR18

Threshold / Carpet Reducer



SWTM8

T-Molding



SQTR8

Quarter Round

Trim images are for illustration purposes only. Actual dimensions will vary. Contact the Shaw Information Center for additional details: 800-441-7429.