



HOME CARPET INDUSTRIES • 800.542.3226 • WHERE THE PROS BUY FLOORING MATERIALS • DALTON GEORGIA




HOME
CARPET INDUSTRIES

2025
ADHESIVE & UNDERLAYMENT CATALOG

Hush III Cork 3 mm

Impact sound control

CT 08V41
PC/SS 203MM
HS 118SA

GOOD BETTER BEST



- Use with hardwood, laminate, ceramic and natural stone
- 100% natural and sustainable cork
- Non-toxic and hypoallergenic
- Naturally resistant to mold and mildew
- Approved for use with SPC or WPC floors with attached pad
- Radiant Heat Approved — subfloor temperature can not exceed 85° for radiant heat installation
- 48" × 50' / 200 ft² / 3 mm (approx. 1/8")

GroundWorks

Acoustical underlayment

CT USC11 Jumbo USC12
PC/SS 5430V Jumbo 5000V
HS 074VS Jumbo 129VS

GOOD BETTER BEST



- Loose-lay GroundWorks and float LVT/LVP or glue GroundWorks and glue LVT/LVP
- Not to be used for grouted LVT installations
- Excellent sound suppression over concrete or wood truss system
- GREENGUARD Indoor Air Quality Certified Suitable for use with radiant heat flooring
- Extends residential wear warranty 5 years on Shaw LVP
- Radiant Heat Approved — Subfloor temperature can not exceed 85° for radiant heat installation
- 3' × 33.34' / 100 ft² per roll
- Also available in jumbo rolls — 6' × 75' / 450 ft²; 1.4 mm thick

Bravo Advanced

Sound reduction & comfort

CT US171
PC/SS 284MM
HS 330SA

GOOD BETTER BEST



- Loose-lay Bravo Advanced and float LVT/LVP or glue Bravo Advanced and glue LVT/LVP
- Not to be used for grouted LVT installations
- Use with luxury vinyl, hardwood and laminate. This product features sound suppression and moisture barrier
- Proper thickness for comfort and stability
- For use over concrete or wood substrates on all grade levels
- Radiant Heat Approved — Subfloor temperature can not exceed 85° for radiant heat installation
- IIC 73 / STC 72
- WVTR rating of 0.11 g/cm²/1,000 ft²/24h
- 43" × 57' / 200 ft² per roll; 1.5 mm thick

Selitac Advanced

For laminate & engineered hardwood

CT US159
PC/SS 281MM
HS 164SM

GOOD BETTER **BEST**



- Superior sound and moisture protection for laminate and engineered hardwood
- Lip and tape feature — tape still needed for end cut transitions (see Quick Guide for tape information)
- End Seams need to be taped with Selistop tape when used over concrete subfloors
- Printed fanfold panels are easy to lay and easy to cut
- Excellent thermal insulation
- IIC-69dB — STC-66dB
- Extends Shaw Laminate residential wear warranty 10 years
- Radiant Heat Approved — subfloor temperature can not exceed 85° for radiant heat installation
- 4' x 25' / 100 ft² per box; 2mm thick

SilentStep Ultra

For laminate & hardwood floating flooring

CT US210
PC/SS 301MM
HS 165SM

GOOD BETTER **BEST**



- Excellent sound and moisture protection for laminate and floating hardwood floors
- 100% closed cell polyolefin foam core with peel and stick seam overlap
- Superior moisture protection
- Stable, will not crumble or deteriorate under flooring
- IIC-73 dB — STC-72 dB
- Extends Shaw residential wear warranty 10 years
- Radiant Heat Approved — subfloor temperature can not exceed 85° for radiant heat installation
- 42" x 28.57' / 100 ft² per roll; 2mm thick

Acoustic

Essential Foam

For laminate & engineered hardwood

CT US193
HS 168SM

GOOD BETTER **BEST**



- Made in the USA
- For use on or above grade level over wood substrate
- Proper thickness for comfort and stability
- Does not support the growth of mold and mildew
- Radiant Heat Approved — subfloor temperature can not exceed 85° for radiant heat installation
- 48" x 25' / 100 ft²

Tri Shield

Multi-use underlayment

CT US195
PC/SS 299MM
HS 332SA

GOOD BETTER **BEST**




- Use with laminate and engineered hardwood
- Mold and mildew resistant
- Provides acoustical value
- Includes overlap and tape for quick and easy installation
- IIC - 67dB / STC - 67dB
- 42" x 28.57' roll / 100 ft² / 2mm thick
- 48 rolls per pallet

2-N-1 Pro Foam

For laminate & engineered hardwood

CT US144
PC/SS 302MM
HS 166SM

GOOD BETTER **BEST**




- Bonded polyethylene layer provides a moisture-retardant barrier to protect your floor
- Proper thickness for comfort and stability
- For use over concrete or wood substrates on all grade levels
- Radiant Heat Approved — subfloor temperature can not exceed 85° for radiant heat installation
- 40" x 60' / 200 ft² per roll

Pet Perfect Resilient Underlayment

Premium LVT underlayment

CT US203
PC/SS 329MM
HS 335SA

GOOD BETTER BEST



- Premium LVT underlayment featuring sound suppression and moisture barrier
- Guards against mold and mildew beneath subfloor
- Lip and tape feature — tape still needed for end cut transitions (see Quick Guide for tape information)
- End seams must be taped with Selitac Tape when used over concrete subfloors
- Smoothes uneven subfloors to save you time and money with no messy prep work
- Thermal insulation makes product great for basements — makes floors feel warmer
- Shock-absorbing technology supports floor locking system - increases comfort
- Fanfold panels lay flat and easy-to-cut grid lines make install simple
- Radiant Heat Approved — subfloor temperature cannot exceed 85° for radiant heat installation
- 3.9' × 25.7' / 100 ft² per box / 1.5mm thick / 56 boxes per pallet

Foundation Plus

Premium acoustical underlayment/crack isolation membrane

CT US235
PC/SS 334MM
HS 331SA

GOOD BETTER BEST



- Ideal for all types of installations. Suitable over concrete or wood subfloors
- For use under: vinyl flooring — tile and plank (including luxury vinyl with attached back), laminate, engineered and solid hardwood, ceramic and porcelain tile
- Moisture guard — prevents spills from getting into the subfloor and allows moisture vapor to escape from beneath
- Mold and mildew guard — antimicrobial; works to inhibit the growth of mold, mildew, and odor-causing bacteria
- Comfort — makes hard surface flooring more enjoyable
- Support — the class-leading extreme density not only resists compression but will perform for the life of the floor
- Easy installation — lays flat and helps mask minor subfloor irregularities; can be used above and below grade
- 3' × 3.33' × .051" (1.3 mm) (100 ft²); compression strength: > 5,000 lbs.
- 50 rolls per pallet

Moisture

6 mil Poly Film

Moisture barrier for concrete floors

CT US101 Jumbo US160
PC/SS 209MM Jumbo 270MM
HS 101SS Jumbo 102SS

GOOD BETTER BEST



- For use over concrete substrates on all grade levels
- Self-sealing tape at seams for easy installation
- Contains recycled content
- Made in the USA
- For floating laminate, hardwood, and luxury vinyl floors
- 46"W × 26.33'L / 100 ft² roll
- 46"W × 104.5'L / 400 ft² roll

Acoustic

Cork 6 mm

Impact sound control

CT 08V40
PC/SS 204MM
HS 101SS

GOOD BETTER BEST



- Use with hardwood, laminate, ceramic and natural stone
- 100% natural and sustainable cork
- Non-toxic and hypoallergenic
- Naturally resistant to mold and mildew
- Radiant heat approved — subfloor temperature can not exceed 85° for radiant heat installation
- 6 mm (approx. 1/4") / 200 ft²/roll; 48" × 50'

Hope

Exceptional value, supports your floor and St. Jude

GOOD BETTER **BEST**



- Enhances the life of your carpet
- Moisture barrier prevents spills and pet accidents from penetrating the cushion for up to 24 hours
- Life of the carpet warranty to original purchaser
- 8 lb., 7/16"
- 6' x 30' / 20 yd²

Charity

Top-selling cushion with memory foam comfort

GOOD BETTER **BEST**




- Memory foam
- Moisture barrier prevents spills and pet accidents from penetrating the cushion for up to 24 hours
- Life of the carpet warranty to original purchaser
- 8 lb., 15/32"
- 6' x 30' / 20 yd²

Courage

Maximum comfort for a luxurious feel

GOOD BETTER **BEST** **PREMIUM**



- ComforTouch™ exceptional comfort underfoot and long-lasting support
- Densified urethane is designed for maximum softness and durability
- Dual moisture barrier offering a 24-hour barrier on both sides of the cushion
- Life of the carpet warranty to the original purchaser
- 1/2" thick
- 6' x 45' / 30 yd²

Victorious Plus

Our flagship, ultra-luxe cushion

GOOD BETTER **BEST** **PREMIUM**



- Luxurious and resilient cushion that maintains original firmness and support
- 10-lb. density frothed urethane for ultimate high performance
- Moisture barrier prevents spills and pet accidents from penetrating the cushion for up to 24 hours
- Life of the carpet warranty to the original purchaser
- 10 lb., 7/16"
- 6' x 45' / 30 yd²

White Hot

Performance cushion for Anderson Tuftex carpet

GOOD BETTER **BEST**



- Moisture barrier prevents spills and pet accidents from penetrating the cushion for up to 24 hours
- Life of the carpet warranty to original purchaser
- 8 lb., 15/32"
- 6' x 37'6" / 25 yd²

Pet Perfect

The perfect pair to Pet Perfect carpet

GOOD BETTER **BEST**



- Moisture-resistant barrier
- Activated carbon for odor control
- Life of the carpet warranty; upgraded warranty when Pet Perfect carpet and Pet Perfect cushion are purchased together
- 8 lb., 0.450"
- 6' x 30' / 20 yd²

Rebond

Choice for comfort and value

- Enhances the life of your carpet
- Soft and affordable

Ruby


GOOD BETTER BEST



Density	8.0 lbs	8.0 lbs	8.0 lbs	8.0 lbs
Thickness	1/4"	3/8"	7/16"	1/2"
Roll Size	6' x 45'	6' x 45'	6' x 45'	6' x 45'
Ft ² /Roll	30	30	30	30
FHA	Class II	Class II	Class II	Class II
Certified				
Insulation	R 0.91	R 1.37	R 1.6	R 1.82
Rating				
Recycled	Yes	Yes	Yes	Yes
Content				
Recyclable	Yes	Yes	Yes	Yes
Cushion	15 year	15 year	15 year	15 year
Warranty				

Ruby Plus


GOOD BETTER BEST



Density	8.0 lbs	8.0 lbs
Thickness	7/16"	1/2"
Roll Size	6' x 45'	6' x 45'
Ft ² /Roll	30	30
FHA	Class II	Class II
Certified		
Insulation	R 1.6	R 1.82
Rating		
Recycled	Yes	Yes
Content		
Recyclable	Yes	Yes
Cushion	15 year	15 year
Warranty		

Superior Plus

GOOD BETTER BEST



Density	7.0 lbs
Thickness	7/16"
Roll Size	6' x 45'
Ft ² /Roll	30
FHA Certified	Class II
Insulation	R 1.8
Rating	
Recycled	Yes
Content	
Recyclable	Yes
Cushion	15 year
Warranty	

Superior

GOOD BETTER BEST



Density	7.0 lbs	7.0 lbs
Thickness	7/16"	1/2"
Roll Size	6' x 45'	6' x 45'
Ft ² /Roll	30	30
FHA Certified	Class II	Class II
Insulation	R 1.8	R 1.8
Rating		
Recycled	Yes	Yes
Content		
Recyclable	Yes	Yes
Cushion	15 year	15 year
Warranty		

Support Plus


GOOD BETTER BEST



Density	6.0 lbs	6.0 lbs	6.0 lbs
Thickness	3/8"	7/16"	1/2"
Roll Size	6' x 45'	6' x 45'	6' x 45'
Ft ² /Roll	30	30	30
FHA Certified	Class I	Class I	Class I
Insulation	R 1.4	R 1.64	R 1.87
Rating			
Recycled	Yes	Yes	Yes
Content			
Recyclable	Yes	Yes	Yes
Cushion	10 year	10 year	10 year
Warranty			

Altima

GOOD BETTER BEST



Density	5.5 lbs
Thickness	7/16"
Roll Size	6' x 45'
Ft ² /Roll	30
FHA Certified	Class I
Insulation	R 1.68
Rating	
Recycled	Yes
Content	
Recyclable	Yes
Cushion	10 year
Warranty	

Tack Strip Concrete 11/16" Nail

Designed for new construction projects

	UNIT	ROLL
CT	USC95	CT201
PC/SS	246MM	142SM
HS	142SM	108SV

GOOD BETTER BEST



- For use in new construction/new concrete
- 100 4' sticks per box/400 linear feet total
- 40 boxes per pallet

Tack Strip Concrete 5/8" Nail

Designed for remodel projects

	UNIT	ROLL
CT	USC93	CT195F
PC/SS	247MM	143SM
HS	143SM	109SV

GOOD BETTER BEST



- For use in remodels/old concrete
- 100 4' sticks per box/400 linear feet total
- 44 boxes per pallet

Tack Strip Wood 3/4"

Used for all wood substrates

	UNIT	ROLL
CT	USC92	CT205F
PC/SS	248MM	144SM
HS	144SM	107SV

GOOD BETTER BEST



- For use on wood subfloors
- 1" wide
- 100 4' sticks per box/400 linear feet total
- 40 boxes per pallet

Tack Strip Elasticel

Designed for gypsum subfloors

	UNIT	ROLL
CT	USC94	CT197SF
PC/SS	285MM	145SM
HS	145SM	

GOOD BETTER BEST



- For use on gypsum subfloors
- 100 4' sticks per box / 400 linear feet total
- 26 boxes per pallet



All tack strip is Shaw branded

Seam Tape

Blue Line Seam Tape



- Roll is 3 5/8" wide x 20 yd long
- Sold by the box; 10 rolls per box

TTT Adhesive Tread-Trim-Tack Strip

Elastomeric tubed adhesive

10.5-oz. 29-oz.
CT US107 US140
PC/SS 249MM 318SA
HS 317SA

GOOD BETTER BEST



- Used with Stair treads, molding trims and tack strip — but can also be used as glue assist for engineered hardwood
- Modified-silane adhesive
- Two-hour curing time
- High bond strength
- Excellent elongation properties
- Spread rate will vary based on application
- Sold by box only
- 10.5-oz. tube / 12 tubes per box / 50 boxes per pallet
- 29-oz. tube; 4 tubes per box; 126 boxes per pallet

35 MC

Premium urethane-based adhesive

CT US117
PC/SS 251MM
HS HS105

GOOD BETTER BEST



- Can be used with mineral-core resilient and engineered hardwood
- No subfloor moisture testing required
- Premium urethane wood flooring adhesive
- Ultimate moisture and sound control
- Ideal for high moisture content slabs
- Crack suppressant
- Low odor — VOC compliant
- Pail includes trowel for moisture control installation
- Excellent green strength
- 35 ft²/gal with enclosed trowel blade — 60 ft²/gal as adhesive only
- 4-gal. pail; 36 pails per pallet

Hardwood Adhesive

No Moisture Test

3-in-1 Ultra

Premium modified silane

CT US118
PC/SS 252MM
HS 111SA

GOOD BETTER BEST



- Can be used with mineral-core resilient and engineered hardwood
- No subfloor moisture testing required when troweled as a moisture barrier
- Crack suppressant
- Ultimate moisture and sound control
- Low odor, low VOC
- Greenguard® certified for indoor air quality
- Clip-on trowel blade provided with each pail
- 35 ft²/gal. for moisture/sound — 60 ft²/gal. as adhesive only
- Easy cleanup with soap and water
- 4-gal. pail; 48 pails per pallet

Tongue & Groove

Acrylic-based tongue & groove adhesive

CT US168
PC/SS 320MM
HS 149SM

GOOD BETTER BEST



- 16-oz. bottle
- Dries clear
- Good water resistance
- Fast setting time
- Easy clean up with water
- Low odor and VOC content
- Approximately 80-100 ft² spread rate per bottle
- 6 bottles per box; 165 boxes per pallet

Urebond Enhanced

Moisture protection up to 95% RH or 12 lbs.

CT US116
PC/SS 253MM
HS 163SM

GOOD BETTER BEST



- Up to 95% RH or 12 lbs (5.44 kg)
- Crack suppression
- Clip-on trowel included for moisture control
- Can be used with: engineered hardwood
- Spread rate: 35 ft² per gallon for moisture control / 50-60 ft²/gal. for bond only
- 4-gal. pail; 48 pails per pallet

Hybrid

Elastomeric adhesive

CT US169
PC/SS 333MM
HS 156SM

GOOD BETTER BEST



- High-strength, elastomeric membrane
- Easy application, easy to trowel
- Solvent and isocyanate-free
- 95% RH moisture protection
- Non-staining, easy-to-clean
- Non-slump formula
- Extremely low odor
- Spread rate: 20-30 ft²/gal. for moisture control / 60 ft²/gal. for bond only (rates differ based on trowel)
- 4-gal. pail; 48 pails per pallet

Shaw 70

Elastomeric adhesive

GOOD BETTER BEST



- Waterproof adhesive bond when fully cured
- High solids—cross-linking technology
- Low VOC
- Immediate tack/wet grab—"Green Strength"
- Strong, elastomeric, flexible bond
- Easy troweling—non-slumping formula
- Meets USGBC LEED EQ Credit 4.1 requirements
- Can be used with engineered hardwood

Soft Surface Adhesive Broadloom

1000 Broadloom

Premium multi-purpose

PC/SS D1000

GOOD BETTER BEST



- Aggressive tack, fast grab
- Permanent, water-resistant bond
- Up to 2 hours working time
- LEED v4 contributing
- 10 lbs./95% RH
- 5-10 pH
- 8-10 yd²/gal.
- 4-gal. pail; 48 pails per pallet

3800 Indoor-Outdoor

For interior and exterior use

PC/SS D3800

GOOD BETTER BEST



- Universal indoor/outdoor adhesive
- Suitable for indoor/outdoor products in residential, light commercial traffic, walk off and entry ways
- Light commercial traffic, residential, walk off and entry way BL: 8-10 yd²/gal. with 1/8" x 1/8" x 1/8" U-notch trowel
- Walk off, entry way TL: 12-15 yd²/gal. with 1/16" x 1/16" x 1/16" square notch trowel
- 8 lbs./90% RH*
- 1-year warranty
- 4-gal. pail; 48 pails per pallet

Broadloom Seam Sealer

Latex broadloom seam sealer

PC/SS D4000

GOOD BETTER BEST



- Broadloom seam sealer
- 550-600 linear feet/qt.
- 1 qt., 22 lbs.; 12 qts. per case

800 Broadloom

Standard broadloom adhesive

PC/SS 504SF

GOOD BETTER BEST



- Permanent, water-resistant bond
- Up to 120-minute working time
- Easy application
- Low VOC, low odor
- Solvent-free
- Antimicrobial technology
- 5 lbs./85% RH
- 5-9 pH
- 8-10 yd²/gal.
- 4-gal. pail; 48 pails per pallet

8300 Seam Sealer

Moisture-impervious carpet seam sealer

PC/SS D8300



- Moisture impervious seam sealer
- 138-150 linear feet
- 8-oz bottle
- 8.5 lbs (12/case)

Carpet Tile

5000 Carpet Tile - LokWorx+

Premium releasable PSA

PC/SS D5000

GOOD BETTER BEST



- Immediate access for light traffic
- Aggressive tack, fast grab
- Releasable adhesive
- Water-resistant bond
- LEED v4 contributing
- 15 lbs. — 97% RH
- 5-11 pH
- 250-350 ft²/gal.
- 1-gal. pail; 180 pails per pallet
- 4-gal. pail; 48 pails per pallet

3000 Carpet Tile - LokWorx

Releasable PSA

PC/SS 280MM

GOOD BETTER BEST



- Immediate access for light traffic
- Aggressive tack, fast grab
- Releasable adhesive
- Water-resistant bond
- LEED v4 contributing
- 10 lbs. — 95% RH
- 5-11 pH
- 250-350 ft²/gal.
- 1-gal. pail; 180 pails per pallet
- 4-gal. pail; 48 pails per pallet

4062 SV Seam Sealer

Designed for fiberglass sheet goods

CT US165
PC/SS 109MA
HS 068VS

GOOD BETTER BEST



- Solvent-free sealer designed for seaming fiberglass sheet goods in direct glue down installations
- Up to 225 linear feet per 8-oz. bottle
- 8-oz. bottle sold individually
- 6 bottles per carton / 108 cartons per pallet

SV350

Multi-purpose PSA adhesive

PC/SS 103MA-4G 105MA-1G
HS 064VS-4G 065VS-1G

GOOD BETTER BEST



- Use with LVT and LVP, Fiberglass Sheet Goods, VCT and PVC Backed Carpet Tile
- Faster flash time
- Cradle to Cradle certified
- 140-350 ft²/gal. spread rate
- Up to 99% RH
- 4-gal. pail; 48 pails per pallet
- 1-gal. pail; 144 pails per pallet

Kwik Flash

Accelerated flash time

CT US108-4G US115-1G
PC/SS 5006V-4G 5005V-1G
HS 080VS-4G 081VS-1G

GOOD BETTER BEST



- LVP / LVT adhesive
- Firm setting transitional adhesive
- Faster flash time
- California SCAQMD Rule 1168
- 140-225 ft²/gal. spread rate
- Up to 95% RH
- 1-gal. pails, 144 pails per pallet
- 4-gal. pails, 48 pails per pallet

DP99

Multi-purpose PSA

CT USC45-4G USC44-1G
PC/SS 106MM-4G 105MM-1G
HS 103LV-4G 102LV-1G

GOOD BETTER BEST



- Use with LVT and LVP, Fiberglass Sheet Goods, VCT and PVC Backed Carpet Tile
- Superior tack & high strength
- Extended working time
- Up to 99% RH
- pH limit 12
- Water-resistant
- LEED V4 contributing
- 140-350 ft²/gal. spread rate
- 4-gal. pails, 48 pails per pallet
- 1-gal. pails, 144 pails per pallet

T-180

Recommended adhesive for installation of attached-pad and dry-back luxury vinyl products

CT US174-4G US173-1G
PC/SS 5026V-4G 207MM-1G
HS 101LV-4G 104LV-1G



- Up to 95% RH
- pH limit 10
- Water-resistant
- LEED V4 contributing
- 140 - 170 ft²/gal. spread rate
- High-strength, high-tack adhesive for luxury vinyl plank and tile
- Extended open time, fast dry time and ease of application
- Outstanding water resistance and tenacious bond strength for demanding installations
- 1-gal. pails, 144 pails per pallet
- 4-gal. pails, 48 pails per pallet


Coordinating Trim

Due to high color variation in all flooring products, it is recommended and necessary to preselect the flooring planks prior to installation. Choose the planks that best match your trim pieces and set them aside prior to installation. This will ensure a uniform final appearance.

Stair Tread System

Durable, waterproof vinyl stair tread with pre-attached stair nosing. This stair tread is an easy, low-maintenance way to add value to your home.



- Matching colors available for majority of resilient flooring products
- Now available in round or square 
- 100% waterproof
- Includes end cap to be cut to size for the right or left side, then adhered to tread for open staircases

- Seamless one-piece stair tread
- Works with closed stairs or stairs with an exposed side profile
- Easy DIY install or professional installation
- 48" length x 12" width x 8.5 mm thick
- 1 piece per carton

Recommended Adhesive

- LokWorx TTT Adhesive:
 - Sold by the box
 - Available in 2 sizes: 10.5-oz. tube (12 tubes per box); 29-oz. tube (4 tubes per box)
- Approximate coverage:
 - 10.5-oz. tube — 3 stairs and 3 risers;
 - 29-oz. tube — 9 stairs and 9 risers
 - Actual coverage will vary depending on each installation

White Stair Riser

CT USC02 PC/SS PCSTR HS LVWRI



- Easy to install
- Cost-effective way to add value to your home
- Installs over existing risers
- White with smooth finish that is paintable
- 48" length x 7.5" width
- Thickness: .56"
- 3 risers per carton



We supply all types of flooring products.
Call your Home Carpet flooring specialists for
quotes and product availability.



WHERE THE PROS BUY FLOORING MATERIALS

Talk to our experts at 800.542.3226 | FAX at 706.277.3385 | homecarpet.com

Prices and product availability are subject to change without notice. We make every effort to ensure the accuracy of the information published in our catalogs and website - but suggest you always call for current prices. Not responsible for typographic errors. Weights and measures may not be exact.

Prices do not include shipping. Find more product info at homecarpet.com or call 800.542.3226. 7.10.2025