

CORETEC® 5"

CP548 Everlast



513 Blonde Oak



207 Rocky Oak



505 Maple Glaze



508 Wild Hickory



501 Linear Pine



205 Seven Oak



504 Dark Oak



507 Walnut Haze



513 Blonde Oak



509 Wheat Oak



511 Wild Pear



201 Exoteak

CORETEC® 5"

Everlast CP548

	US Units	Metric Units
Style Number	CP548	
Construction	Waterproof Foam Core	8mm
Edge Profile	Micro Bevel	0.5mm
Nominal Dimensions	5" wide, 48" long	
Actual Product Width	4.96"	12.6cm
Actual Product Length	48.02"	122cm
Wear Layer Thickness	20 mil (0.02")	0.5mm
Overall Product Thickness	0.314"	8mm
Core Thickness	0.256"	6.5mm
Attached Underlayment	Attached Cork	
Attached Underlayment	0.059"	1.5mm
Thickness		
Finish	UV Acrylic	
Installation Methods	Floating or Direct Glue	
Profile	Angle / Tap	
Country of Origin	Imported	

Area per Box	28.68 SF	2.48 SM
Pieces per Box	16 pieces	
Weight per Box	44.09 lb	19.99 kg
Boxes per Pallet	42 boxes	

Static Load (ASTM F970)	Passes
Residual Indentation (ASTM F1914)	Passes
Resistance to Heat (ASTM F1514)	Passes
Resistance to Light (ASTM F1515)	Passes
Resistance to Chemicals (ASTM F925)	Passes
Smoke Density (ASTM E662)	Passes
Radiant Panel (ASTM E648)	Passes, Class I
Slip Resistance (ASTM D2047)	ADA compliant

Lifetime Limited Warranty
Waterproof Core Commercial Warranty
Commercial Ub Bond 4100/4151

FloorScore Certified
GreenGuard (Certification Gold, Private Label) Certified