

LUXURY VINYL

SKILLS+ (SLV LVP) WW705

Construction	SPC	
Profile	Click	
Size	7" x 48"	17.78 cm x 121.92 cm
Overall Thickness	0.189"	4.8 mm
Wear Layer Thickness	12 mil (0.012")	0.3 mm
Attached Underlayment	EVA Pad	
Attached Underlayment Thickness	0.059"	1.5 mm
Finish	ArmourBead®	
Edge Description	Micro Bevel	
Area per Carton	18.67 sq ft	1.73 sq m
Area per Pallet	1493.6 sq ft	138.76 sq m
Installation Methods	Floating	
Installation Grade	Above, On, Below	
Residential Warranty	30 Year Residential Resilient Limited Warranty	
Commercial Warranty	7 Year Light Commercial	
Installation	Floorte Pro 3 & 5 Installation Guidelines	
Maintenance	Residential Resilient Maintenance	
Radiant Panel (ASTM E648)	Passes, Class I	



Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number



150 Cinnamon Walnut

Color Variation: V3 -
Moderate



154 Almond Oak

Color Variation: V3 -
Moderate



203 Tawny Oak

Color Variation: V4 -
Substantial



556 Smoky Oak

Color Variation: V4 -
Substantial



591 Oyster Oak

Color Variation: V4 -
Substantial



820 Amber Oak

Color Variation: V3 -
Moderate



1056 Driftwood

Color Variation: V3 -
Moderate



1160 Fresh Driftwood

Color Variation: V3 -
Moderate



2013 White Sand

Color Variation: V3 -
Moderate



2014 Marina

Color Variation: V3 -
Moderate

LUXURY VINYL

SKILLS+ (SLV LVP) WW705



2083 Simple Wash

Color Variation: V2 -
Slight



2084 Spalted Maple

Color Variation: V3 -
Moderate



5091 Lighthouse

Color Variation: V3 -
Moderate



7087 Castaway

Color Variation: V3 -
Moderate



7089 Wild Dunes

Color Variation: V3 -
Moderate



7294 Casual Comfort


Color Variation: V2 -
Slight



7295 Modern Classic

Color Variation: V3 -
Moderate

Coordinating Trim



Baby Threshold*

BT3HS | 94"



T-Molding*

TM3HS | 94"



Multi-Purpose
Reducer

RD3HS | 94"



Quarter Round

QTRHS | 94"



Overlap Stairnose

VSSTN | 94"




Flush Stairnose

FS4HS | 94"


Coordinating Metal Trim



Reducer



T-Mold



Stair Cap

Finish

Satin Silver

143SA

146SA

140SA

Satin Nickel

144SA

147SA

141SA

Installation Range

Profile Size

3.5mm

Installation Range

1.5mm to 3.5mm heights

5.5mm

3.6mm to 5.5mm heights

8mm

6mm to 8mm heights



TREADZ®

Center LVCTR

Right LVCAR

Left LVCAL

White Riser LVWRI*

*packages of 3

LUXURY VINYL

PERFECT (PLT LVP) WW707

Construction	WPC	
Profile	Fold-N-Tap	
Size	7" x 48"	17.78 cm x 121.92 cm
Overall Thickness	0.315"	8 mm
Wear Layer Thickness	20 mil (0.02")	0.5 mm
Attached Underlayment	Attached Pad	
Finish	ScuffResist Platinum	
Edge Description	Accent Bevel	
Area per Carton	18.91 sq ft	1.76 sq m
Area per Pallet	1323.7 sq ft	122.98 sq m
Installation Methods	Floating or Direct Glue	
Installation Grade	Above, On, Below	
Color Variation	Yes	
Embossed In Register	Yes	
FloorScore Certified	Yes	
Residential Warranty	Residential Resilient Lifetime Limited Warranty	
Commercial Warranty	10 Year Light Commercial	
Installation	Floorte Classic Installation Guidelines	
Maintenance	Residential Resilient Maintenance	
Radiant Panel (ASTM E648)	Passes, Class I	



LUXURY VINYL

PERFECT (PLT LVP) WW707




Suggested Adhesive

Style Name

Style Number

Shaw T-180 (4 gal)

Coordinating Trim




Baby Threshold*

VSBTB | 94"



T-Molding*

VSTM6 | 94"



**Multi-Purpose
Reducer**

VSMP6 | 94"



Quarter Round

VSQT6 | 94"



Overlap Stairnose

VSST6 | 94"



Flush Stairnose

VFSN5 | 94"

*Packaged with molding track

TREADZ®



Center

LVCTR

Right

LVCAR

Left

LVCAL

White Riser

LVWRI*

*packages of 3



homecarpet.com

800.542.3226

Shaw
FLOORS


LUXURY VINYL

GOLIATH (GLD LVP) WW200

Construction	SPC	
Profile	Fold-N-Tap	
Size	7" x 48"	17.78 cm x 121.92 cm
Overall Thickness	0.197"	5 mm
Wear Layer Thickness	20 mil (0.02")	0.5 mm
Attached Underlayment	EVA Pad	
Attached Underlayment Thickness	0.039"	1 mm
Edge Description	Micro Bevel	
Area per Carton	18.48 sq ft	1.72 sq m
Area per Pallet	1478.4 sq ft	137.35 sq m
Installation Methods	Floating	
Installation Grade	All Levels of the Home	
Environmental	FloorScore® Certified	
Residential Warranty	Residential Resilient Limited Warranty - Defects, Wear, Water	
Commercial Warranty	10 Year Light Commercial	
Installation	Floorte Pro 3 & 5 Series Installation Floorte Pro 6, 7 & 10 Installation	



Coordinating Trim



Baby Threshold*

BT3MB | 94"



T-Molding*

TM3MB | 94"



Multi-Purpose Reducer

RD3MB | 94"



Quarter Round

QTRMB | 94"



Flush Stairnose

FS4MB | 94"

*Packaged with molding track

LUXURY VINYL

GOLIATH (GLD LVP) WW200



2097 Flaxen



homecarpet.com

800.542.3226

Shaw
FLOORS

LUXURY VINYL

LISTED WW565



Construction	WPC	
Profile	Fold-N-Tap	
Size	7" x 48"	17.78 cm x 121.92 cm
Overall Thickness	0.315"	8 mm
Wear Layer Thickness	20 mil (0.02")	0.5 mm
Attached Underlayment	Attached Pad	
Attached Underlayment Thickness	0.059"	1.5 mm
Finish	ArmourBead®	
Edge Description	Pressed Bevel	
Area per Carton	18.81 sq ft	1.75 sq m
Area per Pallet	1316.7 sq ft	122.33 sq m
Installation Methods	Floating or Direct Glue	
Installation Grade	Above, On, Below	
FloorScore Certified	Yes	
Residential Warranty	Residential Resilient Lifetime Limited Warranty	
Commercial Warranty	10 Year Light Commercial	
Installation	Floorte Classic Installation Guidelines	
Maintenance	Residential Resilient Maintenance	
Radiant Panel (ASTM E648)	Passes, Class I	



Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number

LUXURY VINYL

LISTED WW565



Suggested Adhesive

Style Name


Style Number

Coordinating Trim




Baby Threshold*

BT7HS | 94"



T-Molding*

TM7HS | 94"



Multi-Purpose Reducer

RD7HS | 94"



Quarter Round

QTRHS | 94"



Flush Stairnose

FS7HS | 94"

*Packaged with molding track

Coordinating Stair Treads



Stair Tread TRIHS

White Riser LVWRI*

*packages of 3



homecarpet.com

800.542.3226



LUXURY VINYL METROPOLITAN GLUE 20 WW560

Construction	Manufactured LVT <5.0 mm Dryback Residential	
Profile	Direct Glue	
Size	6" x 48"	15.24 cm x 121.92 cm
Overall Thickness	0.098"	2.5 mm
Wear Layer Thickness	20 mil (0.02")	0.5 mm
Finish	ScuffResist	
Edge Description	Square	
Area per Carton	41.72 sq ft	3.88 sq m
Area per Pallet	2002.56 sq ft	186.04 sq m
Installation	Glue	
Installation Grade	Above, On, Below	
Ortho-Phthalates Free	Yes	
FloorScore Certified	Yes	
Residential Warranty	Lifetime	
Commercial Warranty	15 Year Limited Commer Wear Com Ub Bond 4100/S150-95/4151	
Smoke Density (ASTM E662, Flaming Mode)	Passes, <450	
Radiant Panel (ASTM E648)	Passes, Class I	

Colors

				
116 Sweet Auburn	216 Peachtree Street	256 South Beach	559 Hamilton Ave	564 Michigan Ave
				
568 Beaumont St	572 King St	684 Rush Street	740 Broadway	769 Canton St

LUXURY VINYL METROPOLITAN GLUE 20 WW560



774 Lakeshore Dr




775 Music Row

Suggested Adhesive

Style Name	Style Number
LG4100-4GALLON	312VS
KWIKFLASH 4 GAL	080VS
KWIKFLASH LV1	081VS
S150 SPRAY ADHS	069VS
SHAW 200 TPS 4G	026VS
SHAW 200 1 GAL	052VS

Coordinating Trim



Multi-Purpose Reducer*

VSUN1 | 94"



Quarter Round

VSQT1 | 94"

VSQT6 | 94"



Overlap Stairnose

VSSN1 | 94"

VSST6 | 94"




Flush Stairnose

VFSN3 | 94"


*Packaged with molding track

Coordinating Metal Trim




Finish

Reducer



T-Mold



Stair Cap

Satin Silver

152SA

155SA

149SA

Satin Nickel

153SA

156SA

150SA

Dark Bronze

154SA

157SA

151SA

Installation Range

Profile Size	Installation Range
3.5mm	1.5mm to 3.5mm heights
5.5mm	3.6mm to 5.5mm heights



homecarpet.com

800.542.3226

